



NX-8700

The NX-8700 supports 622 Mbps WAN bandwidth and 256,000 flows. The NX-8700 makes application acceleration cost effective in the largest enterprise facilities, such as regional hubs or multinational data centers.

Capacity	
WAN Bandwidth Capacity (all features + encryption)	622 Mbps
Simultaneous Connections	256,000
Resiliency	
Power Supplies	Dual redundant
Network	1+1 and N+1 with VRRP or WCCP
RAM	ECC memory
MTBF	84,600 hours (9.7 years)
Security	
Disk Encryption	128-bit AES
Network Encryption	IPsec (256-bit AES)
Connectivity	
LAN/WAN Ethernet	4 x 10/100/1000 LAN/WAN (2 LAN/ 2 WAN) as per IEEE 802.3i, 802.3u, 802.3ab, 802.1Q 2 x 1/10 Gbps fiber Ethernet data ports (1 LAN / 1 WAN) as per IEEE 802.3z, 802.3ae, 802.1Q
Management	2 x 10/100/1000; Console port
Deployment	
In-line Bridge Mode	In-line between L2 switch and WAN router with fail-to-wire in case of failure (copper only)
Out-of-Path (Router) Mode	Attached to WAN router out-of-path with PBR re-direction, WCCP, and VRRP
Power	
Requirement	100-240VAC / 50-60Hz / 491W / 1675 BTU or less

Power Adapter	1+1 Redundant
Dimensions	
Height	3.4 in (87 mm) or less
Width	17.5 in (444.0 mm) or less
Depth	31.3 in (795 mm) or less
Weight	47.5 lbs (21.5 kg) or less
Regulatory	
EMC	FCC Part 15 Class A, EN 55022 Class A, VCCI Class A, EN 61000-3-2/3-3, 55024
Safety	UL/cUL/60950, EN 60950
Environmental	
Temperature (Operating)	10° C to 35° C (50° F to 95° F)
Temperature (Storage)	-40° C to 65° C (-40° F to 149° F)
Humidity (Operating)	10% to 80% relative humidity, non-condensing
Humidity (Storage)	8% to 95% relative humidity, non-condensing
Altitude (Operating)	Up to 10,000 ft (3,048 m)
Altitude (Storage)	Up to 40,000 ft (12,192 m)
Management	
CLI	Full-featured CLI available over DB-9 console port or SSH
GUI	Web-based Appliance Manager available vis HTTPS (default) or HTTP Global Management Systems (GMS) provides centralized configuration, monitoring, and management of multiple NX appliance
SNMP	SNMPv2c, SNMPv3
Secure Access	SSH and HTTPS
Logging	Syslog with configurable levels. Email alerts
Authentication	Local database, RADIUS, TACACS+
Statistics	Graphing and monitoring, real-time and historical

Company Address

Silver Peak Systems, Inc
2860 De La Cruz Blvd.
Santa Clara, CA 95050

Phone & Fax

Phone: +1 888 598 7325
Local: +1 408 935 1800

Online

Email: info@silver-peak.com
Website: www.silver-peak.com