

Quick Start Guide

• Supplement •

RACK MOUNT INSTRUCTIONS

• EAR MOUNT •

NX-700

NX-1700

EC-XS

Before You Begin

- Check your packing slip to verify that you have all the necessary items.
- Make sure you have a standard Phillips screwdriver.
- You can mount the chassis in either a **2-post telco rack** or a **4-post server rack**.
- If your rack requires its own screws and/or nuts, then use those instead.



Silver Peak Systems, Inc.
2860 De La Cruz Blvd, Suite 100
Santa Clara, CA 95050

1.877.210.7325 (toll-free in USA)
+1.408.935.1850
www.silver-peak.com/support

These instructions show the NX-700 as the example.

The appliance fits into 1 RU of rack space.

The appliance ships with the following:

- Two (2) metal brackets and six (6) black screws to attach them to the appliance.
- Four (4) M5 x 5/8" screws and four (4) cage nuts for mounting the appliance in a rack.
- Four (4) stick-on rubber feet. To position the appliance on a desktop instead of a rack, adhere the feet in the round indentations in the bottom of the appliance.

To mount the appliance into the telco or server rack:


1. Align the three holes in the appliance with the holes in the brackets.



2. Secure the bracket to the appliance with three screws.



3. In the same manner, attach the other bracket to the other side.
4. Attach the cage nuts to the rear of the front rack posts.



5. Use the screws to secure the chassis to the outside front of the rack.